

Navihalter Honda VFR 1200 X Crosstourer

starting MY 2016

Important note:

**The higher the adjustable windshield is positioned,
the more can occur at rough road bumps briefly oscillations of the Navi.**


**When installing the navigation system on the disc carrier of your Honda Crosstourer 1200 (model 2016>) and thus in
the optimal driver's field of view, these vibrations are unavoidable.**

**Using our holder in combination with lockable supply parts or windshields from other manufacturers, vibrations can
be amplified by using rubber bumpers and moving the position of the Navi towards the driver.**

Assembly Instructions

- Remove the rubber caps from the windshield screws and remove the windshield
- Remove plastic washers from the original screws and attach them to the supplied M5 x 22 screws
- Guide the screws through the holes in the windshield and insert the black plastic washers from below onto the screws
- Check on the windshieldmounting whether the dowels are in the upper area of the mounting holes
- Place the Navihalter on the dowels and screw the windshield back on. (max. 2,5 Nm torque)
- Move the windshield to the lowest position, and position the navigation system by moving the swiveling adapter plate directly over the cockpit superstructure

(adapter plate can be turned around if needed)



- Finally adjust the angle of inclination for the attached navigation device and tighten the screws of the plastic-mounted friction hinges as required (adjustable or fixed) evenly